



WATER PROOFING



Features



Repair concrete cracks for water-stop



Deeper penetration



Low VOC content



Reduced odor

SMARTBLOK PU 2K INJECT GROUT


Polyurethane injection grout as a resin for the elastic sealing of cracks in concrete structures

AREAS OF APPLICATION

- **SmartBlok PU 2K INJECT GROUT** is a two component solvent free, polyurethane system consisting of a resin component (Part A) and a special type of isocyanate (Part B)
- This system is ideally suitable for the elastic sealing of cracks in concrete surfaces as well as areas suffering from water leakage problems.
- The use of SmartBlok PU 2K Inject Grout as such is depending on the amount of water expected. In case the crack is dry or moist, the resin can be used directly into the crack



For Ceilings



Live Leakages

5 BENEFITS

- Can be easily drilled and injected
- Flexible resin to withstand crack movements
- Permanent solution to water seepage
- Non-destructive water stoppage
- Eco-friendly

DOSAGE

- Minimum 2 to 4 hours and maximum 24 hours (any dust that settles over the primer should be cleaned before the next application)

BEST BEFORE

- 12 months

TECHNICAL SPECIFICATIONS

Properties	Coreseal 135A	Coreseal 135B
Colour	Yellowish	Dark Brown
Density (g/cc)	1.040 ± 0.02	1.220 ± 0.02
Mixed Viscosity of the mixture at 30°C mPas	250 - 600 cps	250 - 600 cps
Mixing Ratio by volume	2	1
Potlife at 20°C (minutes)	150 minutes	150 minutes
Shore Hardness	40 A	40 A
Mixed Density (g/cc)	1.078	1.078

PACK SIZE

16kgs pack(10kgs part A and 6kgs part B)



World's No.1 Eco Friendly Cement Company

MARKETED BY: **JSW Green Cement Pvt. Ltd.**
Babukhan Millenium Centre, 6-3-1099/1100, No. 702, Block-A, Somajiguda, Hyderabad,
Telangana, India, Pincode - 500 082.

Email: info@jswcement.in | Website: www.jswcement.in | Toll free - 18002662661

SCAN HERE FOR TDS



SCAN HERE

